



BWA-750

BODY WEAR ANTENNA

For Manpack & Handset Military
UHF to VHF Radios



CONFORMITY TO STANDARD OF

- ✓ MIL-STD-810E
- ✓ ISO/TS 16949
- ✓ SO 14001
- ✓ GAMT13 & EG13
- ✓ ISO 9001
- ✓ QS 9000

AVAILABLE ELECTRICAL CONNECTION

Mounting: Compliant with standard accessories vest

OTHER SPECIFICATIONS

Packaging : Individual commercial packaged

FS - MAIN SPECIFICATION AND PERFORMANCES

Application	Tactical Antenna	
Frequencies range	BWA-UHF	225 à 470 MHz
	BWA-VHF	30 à 108 MHz
Impedance	50	Ω
VSWR	BWA-UHF	< 2
	BWA-VHF	< 3.5
Power handling	10	W
Polarisation	vertical	
Connector	BWA-UHF	SMA female
	BWA-VHF	BNC female
Weight	BWA-UHF ⁽¹⁾	70 ± 10 g
	BWA-VHF ⁽¹⁾	140 ± 10 g
Temperature range	- 55 to +70	°C
Salt fog	96	h

⁽¹⁾ without vest

This document belongs exclusively to FIAMM Group and cannot be reproduced without FIAMM Group written agreement
FIAMM reserves the right to change characteristics and specification of this product without notice.